



**APPROACH TABLE**

APPROACH TYPE	Appr. Width*		Min.** Radius
	Min.	Max.	
Residential, Three or More	24'	30'	20'
Commercial (One Way)	20'	30'	20'
Commercial (Two Way)	24'	40'	20'

\* Does not include 2' gravel shoulder on each side of approach.  
 \*\* Or based on applicable commercial design vehicle.

**NOTES:**

1. APPROACHES SPACING SHALL CONFORM TO SECTION 3000 OF THE ACCHD MANUAL.
2. INGRESS/EGRESS BY FORWARD MOTION ONLY.
3. CULVERT PIPE SHALL BE 12" MIN. DIAMETER. CULVERT PIPE SHALL EXTEND TO THE INTERSECTION OF THE DITCH LINE AND THE 4:1 APPROACH FORESLOPE. PIPE MATERIAL SHALL BE EITHER 0.064" THICK CORRUGATED STEEL, 0.060" CORRUGATED ALUMINUM OR CLASS V REINFORCED CONCRETE.

**COMMERCIAL APPROACH AND ACCESS  
 SERVING 3 OR MORE PROPERTIES**

N.T.S.

STANDARD DRAWING No. ACCHD-106  
 CANYON COUNTY HIGHWAY DISTRICTS  
 CANYON COUNTY, IDAHO

REVISED 12/08